

### HIGH TEMPERATURE

- Low-cost alternative to stainless steel and carbon steel housings
- Durable glass-reinforced nylon construction
- 3/4" NPT inlet/outlet and 10" length
- Install unit after hot water heater to reduce suspended sediment



WH34

Model #	Part #	Sump	Cap	I/O	Overall Dimensions	Operating Pressure(psi)	Operating Temperature (deg. F)	Optional Accessories Model #
WH34	152009	Red	Red	3/4" NPT	5-1/8" x 12-1/8"	30-125	30-160	WMB34, WW34

### STAINLESS STEEL

- Ideal for a wide range of residential, commercial and industrial high temperature and high-pressure applications
- Brushed 304 stainless steel sump with cast brass/nickel plated cap
- 3/4" NPT inlet/outlet
- Available in 10", 20" and 30" lengths



Note: Uses standard 10" double open end cartridges. One cartridge for 10" length, two cartridges for 20" length and three cartridges for 30" length.

Model #	Part #	Sump	Cap	I/O	Overall Dimensions	Operating Pressure(psi)	Operating Temperature (deg. F)	Optional Accessories Model #
ST-1	156017-02	304 Stainless Steel	Brass/Nickel Plated	3/4" NPT	4-1/8"x12-7/8"	30-250	40-300	156037
ST-2	156018-02	304 Stainless Steel	Brass/Nickel Plated	3/4" NPT	4-1/8"x22-3/4"	30-250	40-300	156037
ST-3	156019-02	304 Stainless Steel	Brass/Nickel Plated	3/4" NPT	4-1/8"x32-3/8"	30-250	40-300	156037

Available in many sizes and styles, our high temperature housings are manufactured from durable materials with proven performance, including glass-reinforced nylon and stainless steel.